



## The Family

**LS-Series** is a family of subwoofers specially designed for portable or permanent high demand applications. They are made of birch plywood 15mm and 18mm . Speaker grills are from galvanized steel painted with electrostatic paint to be used also for outdoor applications.

## Description

The **LS-118** is a compact subwoofer in the **LS-Series** family.

It has been designed to deliver maximum performance for its size. Can be used in combination with all of our speakers

## Application

Subwoofer

## Specifications

FREQUENCY RESPONSE	32Hz - 120Hz +/- 3dB
SENSITIVITY @ 1w/1m	98dB
MAXIMUM OUTPUT	133dB
AMPLIFIER-PROCESSING	1400-2000w@ 8ohm
POWER AES/CONTINUOUS	1000W/1400W
CROSSOVER FREQUENCY	HPF 30Hz 12db/oct LPF 80-120Hz 24db/oct
DRIVER COMPONENTS	LF 18" ferrite woofer 4"VC 8Ω (optional 4Ω)
ENCLOSURE MATERIAL	Birch plywood 15mm/18mm
ENCLOSURE TYPE	Bass-Reflex
INPUTS	2x NL4 Neutrik
DIMENSIONS HxWxD	540 x 730 x 600 mm
WEIGHT	38kg
FINISHES	Black or White texture paint